




Hele tõrvaõli

Light tar oil

- ✓ Natural components
- ✓ Decorative effect
- ✓ Deep penetration
- ✓ Protects from weather impact.
- ✓ Creates a water-repellent surface



Description	
Properties	<p>Natural compound for the protection and decorative finishing of outdoor wooden surfaces.</p> <ul style="list-style-type: none"> ✓ Based on linseed oil and pine tar. ✓ Gives wood a refined appearance, creating a beautiful transparent coating with a golden-brown hue. ✓ Penetrates the wood well. ✓ Creates a water-repellent surface. ✓ Keeps the treated surface dry, preventing wood from rot. ✓ Protects wood from cracking and the weather impact. ✓ Has a characteristic natural tar smell. <p>Maximum permissible EU VOC content for the product (subcat. e) 400 g/L. Maximum VOC content in the product <400 g/L.</p>
Purpose	<p>Treating wooden items and structures: log constructions, siding boards, garden furniture, greenhouses, terraces, verandas, fences, wooden barrels and pools, structures on children's playgrounds etc. Do not use on previously painted or varnished surfaces.</p>
Types of surfaces	<p>Vacuum-treated and thermally treated wood as well as untreated wood of any species.</p>
Quality standards and labels	<ul style="list-style-type: none"> ✓ VOC (volatile organic compounds) – content in accordance with the European Union directive 2004/42/CE. ✓ Product and service quality is guaranteed by the quality, environmental protection, occupational health and safety management system in accordance with standards ISO 9001:2015; ISO 14001:2015 and OHSAS 18001:2007.
Product specifications	

Surface preparation before treatment	<p>Wood moisture content must not exceed 20%. Perform application at the temperature above 5 °C and relative humidity up to 80%. Clean the surface thoroughly from dirt, grease and dust. The wood must not be damaged by mould and algal growth.</p> <p>Use the wood cleaning agent WoodClean or anti-mould agent Biotol E to pre-treat the surfaces damaged with blue stain or mould.</p> <p>We recommend priming the surface with Biostop primer before applying the product.</p> <p>Clean previously painted surfaces completely, using a scraper, a stiff brush, a heat gun or varnish remover OPS Pro.</p> <p>Remove the darkened areas of the wood mechanically, using a stiff brush, and replace dead wood. Use galvanised fasteners for fastening the treated wooden parts.</p> <p>We do not recommend performing the application in direct sunlight or at high temperatures.</p> <p>Please pay attention to the constructional methods of protecting wooden surfaces: good waterproofing of walls and the roof, water drainage and ventilation. The result of using wood protection products depends on the adequate use of constructional methods of the protection of wooden surfaces.</p>
Application	<p>Do not dilute. Stir the product thoroughly before use. Apply the product evenly from edge to edge along the grain. Take special care to treat the ends. Remove the unabsorbed excess product with a cloth.</p> <p>Apply 1–4 coats, sanding between the coats, depending on the quality and use of the wood. Use the product from one batch. When different batches are used on the same surface, the product must be mixed in a single container to ensure that the colour is even. We recommend treating surfaces exposed to the weather impact once per year.</p>
Colour	Light brown
Consumption	Per one coat: 3–5 m ² /L for sawn wood; 5-10 m ² /L for planed wood.
Thinner	Turpentine Männitärpentin
Drying time	1–7 days depending on weather conditions and the condition of the wood (when applied with a brush).
Tools	Brush, cloth, sponge
Tool cleaning	Wash tools with turpentine Männitärpentin after completing work.
Information	
Frost resistance	Not frost-resistant
Min shelf life	2 years
Storage conditions	Store in a tight container at the temperature between +5°C and +30°C. Protect from direct sun, light and frost.
Safety precautions	 <p>Warning. Harmful to aquatic life with long lasting effects. Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction. Contains 3-iodo-2-propynyl butylcarbamate, tar, pine. Keep out of reach of children. Wear protective gloves/protective clothing/eye protection/face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If medical advice is needed, have product container or label at hand. UFI: N830-F07S-S00W-YOQY.</p>
Waste treatment	<p>Avoid release to the environment. Dispose of the contents/containers in accordance with the current legislation on waste treatment. Contains linseed oil. Oily rags, waste, and other oily materials can cause spontaneous combustion fires if not handled properly. Spray dust, cloth and other contaminated material should be wetted and placed in a metal container. Store in a fire-proof place.</p> <p>Waste treatment methods: code 08 01 11* - Waste paint and varnish containing organic solvents or other dangerous substances. Waste class (Regulation (EU) No 1357/2014): Dangerous.</p>
Density	0,9 kg/L
Volume/weight	1 L – 5 L
<p>The information concerning the product is based on the results of laboratory tests and practical use of the product depending on the location and conditions of its use. As the manufacturer, we guarantee the quality of the product and provide the best recommendations for its appropriate application. As the manufacturer, we cannot control the conditions and circumstances of product transportation, storage and application and numerous other factors that affect its use. Thus, we shall not bear responsibility for the damage caused by ignoring the instructions for use or transportation, by noncompliance with storage conditions and timeframes or by inappropriate application of the product. The manufacturer reserves the right to alter product information at their discretion without prior notice. For additional information, please contact us: http://eskaro.ee/kontaktid/main_office_contacts/</p>	