



Männitärpentin

Pine oil turpentine

- ✓ For thinning alkyd varnishes, paints and oil fillers
- ✓ Cleans the painting tools



Description	
Properties	Oil of turpentine for diluting oil-base and alkyd products ✓ Produced from pine resin ✓ Evaporates from the product slowly, slowing down the drying process ✓ Improves the spread of materials on the surface ✓ Alone, turpentine is used for cleaning and degreasing surfaces and removing stains
Purpose	Solvent for oils as well as oil-base and alkyd (pentaphtol) paints, varnishes and preservatives, tar and other oil-base products. Also used for removing stains as well as cleaning and degreasing surfaces. Not to be used for medical or hygienic purposes!
Quality standards	✓ Product and service quality is guaranteed by the quality, environmental protection, occupational health and safety management system in accordance with standards ISO 9001:2015; ISO 14001:2015 and ISO 45001:2018
Product specifications	
Application	When thinning paints and varnishes, follow the instructions for use attached to them. When removing stains and degreasing, make sure that the surface to be treated can withstand the solvent.
Color	Transparent.
Information	
Frost resistance	Frost-resistant.
Storage conditions	Store in a tightly closed container in a well-ventilated place at a temperature < 30 °C. Protect from direct sunlight.

Safety precautions	 DANGER Harmful if swallowed, in contact with skin or if inhaled. Toxic to aquatic life with long lasting effects. May be fatal if swallowed and enters airways. Causes serious eye irritation. Flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Contains Turpentine, oil; Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics. Wear protective gloves/protective clothing/face protection. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. IF SWALLOWED: Immediately call a POISON CENTER/doctor. UFI: DN10-U047-Y00G-DHNR. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of fire: Use ABC powder extinguisher to extinguish. Store in a well-ventilated place.
Waste treatment	Do not empty into drains. Avoid release to the environment. Dispose of packaging, dry general and hazardous liquid paint waste in accordance with local regulations.
Density	0,8 kg/L
Volume/weight	0,5 L – 1 L
The information concerning the product is based on the results of laboratory tests and practical use of the product depending on the location and conditions of its use. As the manufacturer, we guarantee the quality of the product and provide the best recommendations for its appropriate application. As the manufacturer, we cannot control the conditions and circumstances of product transportation, storage and application and numerous other factors that affect its use. Thus, we shall not bear responsibility for the damage caused by ignoring the instructions for use or transportation, by noncompliance with storage conditions and timeframes or by inappropriate application of the product. The manufacturer reserves the right to alter product information at their discretion without prior notice. For additional information, please contact us: https://eskaro.ee/en/contact/	