



OPS PRO

Paint Stripper

- ✓ Highly effective paint removal agent
- ✓ Ideal for application on vertical surfaces
- ✓ Suitable for both interior and exterior use



Description	
Properties	Paint Stripper <ul style="list-style-type: none"> ✓ Highly effective for removing paints and varnishes. ✓ Free from methylene chloride and methylpyrrolidone. ✓ Its unique gel formulation makes it ideal for application on vertical surfaces. ✓ Suitable for both interior and exterior use.
Purpose	The product is used to soften and remove old paint and varnish coatings from mineral, metal, and wooden surfaces. It effectively removes alkyd, oil-based, and polyurethane paints, as well as water-based coatings, including textured coatings and adhesives. The product is also used to remove graffiti from unpainted surfaces. Under normal conditions, it does not alter the colour of mineral or wooden substrates.
Types of surfaces for use	Suitable for painted mineral, metal, and wooden surfaces. Use with caution on plastic surfaces (e.g. polystyrene, PVC, etc.); always test the product on an inconspicuous area before application. Do not use on aluminium surfaces.
Quality standards	<ul style="list-style-type: none"> ✓ Product and service quality is guaranteed by the quality, environmental protection, occupational health and safety management system in accordance with standards ISO 9001:2015; ISO 14001:2015 and ISO 45001:2018.
Product specifications	
Application	Before use, protect all surfaces that are not intended to be treated. Apply the product evenly in a thick layer (0.5–2 mm) using a natural bristle brush, roller, or spatula. Allow it to act for 15–45 minutes, or until the coating blisters and softens. The required dwell time depends on the type and thickness of the coating to be removed. In some cases, several hours may be required. Remove the softened coating using a spatula, scraper, or wire wool. A pressure washer may also be used. If necessary, apply a second coat of the product. Lightly scoring or scratching the coating before application will improve penetration and increase the speed and effectiveness of the stripping process. When working on vertical surfaces, remove the coating from the bottom upwards. To enhance the softening effect, especially in direct sunlight or windy conditions, cover the treated surface with polyethylene film. After treatment, thoroughly wash the cleaned surface with water and allow it to dry completely. Do not use at temperatures below 0 °C.
Consumption	One litre of the product covers approximately 0.5–3 m ² per coat, depending on the type and thickness of the coating being removed.
Dilution	The product is ready to use.

Tools	Natural bristle brush, short-nap paint roller, putty knife.
Tool cleaning	Clean tools with water and soap.
Additional information	
Frost resistance	None.
Storage conditions	Store and transport in the tightly closed original container in a cool, well-ventilated place at temperatures between 5 and 30 °C. Protect from freezing and direct sunlight. Keep away from heat sources, hot surfaces, sparks, open flames, and other ignition sources.
Safety precautions	  <p>Warning. Flammable liquid and vapour. May cause drowsiness or dizziness. Contains n-butyl acetate and butanone. Repeated exposure may cause skin dryness or cracking. Wear protective gloves, protective clothing, eye protection, and protective footwear. IF INHALED: Move the person to fresh air and keep in a position comfortable for breathing. If medical advice is needed, have the product container or label at hand. UFI: 4QY5-C0DQ-R00R-GJGV. Store in a well-ventilated place. Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. In case of fire: Use ABC dry powder extinguisher for extinguishing. Keep out of reach of children.</p>
Waste treatment	Avoid release to the environment. Dispose of the contents/containers in accordance with the current legislation on waste treatment. Waste treatment methods: code 08 01 12- Waste paint and varnish other than those mentioned in 08 01 11, waste class (Regulation (EU) No 1357/2014): non-dangerous.
Density	0,97 g/cm ³
Volume/weight:	0,75 L
<p>The information concerning the product is based on the results of laboratory tests and practical use of the product depending on the location and conditions of its use. As the manufacturer, we guarantee the quality of the product and provide the best recommendations for its appropriate application. As the manufacturer, we cannot control the conditions and circumstances of product transportation, storage and application and numerous other factors that affect its use. Thus, we shall not bear responsibility for the damage caused by ignoring the instructions for use or transportation, by noncompliance with storage conditions and timeframes or by inappropriate application of the product. The manufacturer reserves the right to alter product information at their discretion without prior notice. For additional information, please contact us: https://eskarogroup.com/en/contact/</p>	