



White Spirit

Solvent

- ✓ For thinning alkyd varnishes, paints and oil fillers
- ✓ Cleans the painting tools
- ✓ Degreases the surface



Description	
Properties	Solvent for solventborne paints and varnishes. ✓ Used for thinning alkyd and oil-based paints and varnishes. ✓ Virtually free of aromatic hydrocarbons. ✓ Low odor. ✓ Degreases the surface. ✓ Cleans the painting tools.
Purpose	For thinning alkyd, oil, urethane alkyd paints and varnishes and oil putties. Not suitable for thinning water-based products. For cleaning painting tools and degreasing surfaces.
Quality standards	✓ Product and service quality is guaranteed by the quality, environmental protection, occupational health and safety management system in accordance with standards ISO 9001:2015; ISO 14001:2015 and ISO 45001:2018.
Product specifications	
Application	Before diluting solvent-based paint products, read their instructions for use. Add White Spirit to the product gradually to avoid overdosing. Clean painting tools with solvent immediately after finishing work. When cleaning surfaces from oil or grease, first test on a small area to ensure White Spirit is suitable for cleaning the surface. Work in a well-ventilated area. Follow safety requirements during use.
Color	Colorless, transparent.
Information	
Frost resistance	Frost-resistant.
Storage conditions	Store in a tightly closed container in a well-ventilated place at a temperature < 30 °C. Protect from direct sunlight.
Safety precautions	 DANGER. May be fatal if swallowed and enters airways. Repeated exposure can cause dryness and cracking of the skin. Keep out of the reach of children. Avoid contact with eyes, skin or clothing. Wear protective gloves / protective clothing / eye protection / face protection. If swallowed, call a poison control center or specialist / physician immediately. UFI AF30-F0MK-D00V-9PW3 Do not induce vomiting. Store locked up. In case of fire: Use an ABC class dry powder extinguisher for extinguishing. It is NOT RECOMMENDED to use tap water as an extinguishing agent

Waste treatment	Do not empty into drains. Avoid release to the environment. Dispose of packaging, dry general and hazardous liquid paint waste in accordance with local regulations.
Density	0,76 kg/L
Volume/weight	0,5 L – 1 L
The information concerning the product is based on the results of laboratory tests and practical use of the product depending on the location and conditions of its use. As the manufacturer, we guarantee the quality of the product and provide the best recommendations for its appropriate application. As the manufacturer, we cannot control the conditions and circumstances of product transportation, storage and application and numerous other factors that affect its use. Thus, we shall not bear responsibility for the damage caused by ignoring the instructions for use or transportation, by noncompliance with storage conditions and timeframes or by inappropriate application of the product. The manufacturer reserves the right to alter product information at their discretion without prior notice. For additional information, please contact us: https://eskaro.ee/en/contact/	