

Safety data sheet This SDS is an English translation of Regulation (EU) nº 2020/878, without any country-specific legislation

2WBL-IN/EX-M105 Granit Lakk Aqua

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING 1.1 Product identifier: Granit Lakk Aqua Other means of identification: Non-applicable 1.2 Relevant identified uses of the substance or mixture and uses advised against: Relevant uses: Lacquer for stone surfaces Uses advised against: All uses not specified in this subsection or in subsection 7.3 1.3 Details of the supplier of the safety data sheet: Eskaro AS Fosforiidi 20 74114 Maardu - Estonia Phone: +372 621 7969 - Fax: +372 621 7968 productsafety.ee@eskaro.com www.eskaro.com 1.4 **Emergency telephone number:** European emergency number - 112

SECTION 2: HAZARDS IDENTIFICATION**

2.1 Classification of the substance or mixture: CLP Regulation (EC) No 1272/2008: The product is not classified as hazardous according to CLP Regulation (EC) No 1272/2008. 2.2 Label elements:

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Hazard statements:

Non-applicable

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment.

Supplementary information:

EUH208: Contains 1,2-benzisothiazol-3(2H)-one, 2-methylisothiazol-3(2H)-one, Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of chemical products

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification		Chemical name/Classification			
CAS: 2634-33-5	1,2-benzisothiazol-3((2H)-one ⁽¹⁾	ATP CLP00		
EC: 220-120-9 Index: 613-088-00-6 REACH: 01-2120761540-60- XXXX	Regulation 1272/2008	Acute Tox. 4: H302; Aquatic Acute 1: H400; Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Danger	٩	<0.05 %	

⁽¹⁾ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2020/878



Safety data sheet This SDS is an English translation of Regulation (EU) n^{o} 2020/878, without any country-specific legislation

2WBL-IN/EX-M105 Granit Lakk Aqua

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

	Identification		Chemical name/Classification				
EC:	55965-84-9 Non-applicable	Reaction mass of 5-c one (3:1) ⁽¹⁾	hloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-	ATP ATP13			
	613-167-00-5 Non-applicable	Regulation 1272/2008	Acute Tox. 2: H310+H330; Acute Tox. 3: H301; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1C: H314; Skin Sens. 1A: H317; EUH071 - Danger		<10.0015%		
	2682-20-4	2-methylisothiazol-3	(2H)-one ⁽¹⁾	ATP ATP13			
Index: REACH:	220-239-6 613-326-00-9 01-2120764690-50- XXXX	Regulation 1272/2008	Acute Tox. 2: H330; Acute Tox. 3: H301+H311; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1B: H314; Skin Sens. 1A: H317; EUH071 - Danger		<0.0015 %		

⁽¹⁾ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:



SECTION 5: FIREFIGHTING MEASURES (continued)

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

it is recommended to avoid environmental spillage of both the product and its container

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

- A.- Technical measures for storage
 - Minimum Temp.:5 °CMaximum Temp.:30 °C
- B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):



SECTION 7: HANDLING AND STORAGE (continued)

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

There are no applicable occupational exposure limits for the substances contained in the product

DNEL (Workers):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
1,2-benzisothiazol-3(2H)-one	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 2634-33-5	Dermal	Non-applicable	Non-applicable	0,966 mg/kg	Non-applicable
EC: 220-120-9	Inhalation	Non-applicable	Non-applicable	6,81 mg/m ³	Non-applicable
2-methylisothiazol-3(2H)-one	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 2682-20-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 220-239-6	Inhalation	Non-applicable	0,043 mg/m ³	Non-applicable	0,021 mg/m ³

DNEL (General population):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
1,2-benzisothiazol-3(2H)-one	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 2634-33-5	Dermal	Non-applicable	Non-applicable	0,345 mg/kg	Non-applicable
EC: 220-120-9	Inhalation	Non-applicable	Non-applicable	1,2 mg/m ³	Non-applicable
2-methylisothiazol-3(2H)-one	Oral	0,053 mg/kg	Non-applicable	0,027 mg/kg	Non-applicable
CAS: 2682-20-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 220-239-6	Inhalation	Non-applicable	0,043 mg/m ³	Non-applicable	0,021 mg/m ³

PNEC:

Identification				
1,2-benzisothiazol-3(2H)-one	STP	1,03 mg/L	Fresh water	0,00403 mg/L
CAS: 2634-33-5	Soil	3 mg/kg	Marine water	0,000403 mg/L
EC: 220-120-9	Intermittent	0,0011 mg/L	Sediment (Fresh water)	0,0499 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,00499 mg/kg
2-methylisothiazol-3(2H)-one	STP	0,23 mg/L	Fresh water	0,00339 mg/L
CAS: 2682-20-4	Soil	0,047 mg/kg	Marine water	0,00339 mg/L
EC: 220-239-6	Intermittent	0,00339 mg/L	Sediment (Fresh water)	Non-applicable
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION** (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Protective gloves against minor risks	CATI		Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+A1:2010 and EN ISO 374- 1:2016+A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing	CATI		Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes	CAT II	EN ISO 20347:2012	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	0 % weight
V.O.C. density at 20 °C:	0,01 kg/m³ (0,01 g/L)
Average carbon number:	4
Average molecular weight:	115,15 g/mol
With regard to Directive 2004/42/EC, this	s product which is ready to use has the following characteristics:
V.O.C. density at 20 °C:	< 130 g/L
EU limit for the product (Cat. A.E):	130 g/L (2010)

Components: Non-applicable

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Version: 5 (Replaced 4)

 Physical state at 20 °C: Appearance: Colour: Odour threshold: Volatility: Boiling point at atmospheric pressure Vapour pressure at 20 °C: Vapour pressure at 20 °C: Evaporation rate at 20 °C: Product description: Density at 20 °C: Relative density at 20 °C: Kinematic viscosity at 20 °C: Kinematic viscosity at 20 °C: Kinematic viscosity at 40 °C: Concentration: pH: Vapour density at 20 °C: Partition coefficient n-octanol/water Solubility in water at 20 °C: Solubility properties: Decomposition temperature: Melting point/freezing point: Flammability: Flash Point: Flammability (solid, gas): Autoignition temperature: Lower flammability limit: Upper flammability limit: Upper flammability limit: Upper flammability limit: Derticle characteristics: Median equivalent diameter: 2 Other information: Explosive properties: Corrosive to metals: Heat of combustion: Ausonala tatal acuestates (by speep) 		
Colour: Odour: Odour threshold: Volatility: Boiling point at atmospheric pressure Vapour pressure at 20 °C: Vapour pressure at 20 °C: Evaporation rate at 20 °C: Evaporation rate at 20 °C: Product description: Density at 20 °C: Relative density at 20 °C: Kinematic viscosity at 20 °C: Kinematic viscosity at 20 °C: Kinematic viscosity at 40 °C: Concentration: pH: Vapour density at 20 °C: Partition coefficient n-octanol/water Solubility in water at 20 °C: Solubility properties: Decomposition temperature: Melting point/freezing point: Flammability: Flash Point: Flammability (solid, gas): Autoignition temperature: Lower flammability limit: Upper flammability limit: Upper flammability limit: Corrosive to metals: Corrosive to metals: Heat of combustion:		Liquid
Odour:Odour threshold:Volatility:Boiling point at atmospheric pressureVapour pressure at 20 °C:Vapour pressure at 20 °C:Evaporation rate at 20 °C:Product description:Density at 20 °C:Relative density at 20 °C:Dynamic viscosity at 20 °C:Kinematic viscosity at 20 °C:Kinematic viscosity at 40 °C:Concentration:pH:Vapour density at 20 °C:Partition coefficient n-octanol/waterSolubility in water at 20 °C:Solubility properties:Decomposition temperature:Melting point/freezing point:Flammability:Flash Point:Flammability (solid, gas):Autoignition temperature:Lower flammability limit:Upper flammability limit:Particle characteristics:Median equivalent diameter:2Other information:Information with regard to physExplosive properties:Oxidising properties:Corrosive to metals:Heat of combustion:		Characteristic
Odour threshold:Volatility:Boiling point at atmospheric pressureVapour pressure at 20 °C:Vapour pressure at 20 °C:Evaporation rate at 20 °C:Product description:Density at 20 °C:Relative density at 20 °C:Kinematic viscosity at 20 °C:Kinematic viscosity at 20 °C:Kinematic viscosity at 40 °C:Concentration:pH:Vapour density at 20 °C:Partition coefficient n-octanol/waterSolubility in water at 20 °C:Solubility properties:Decomposition temperature:Melting point/freezing point:Flammability:Flash Point:Flammability (solid, gas):Autoignition temperature:Lower flammability limit:Upper flammability limit:Particle characteristics:Median equivalent diameter:2Other information:Information with regard to physeExplosive properties:Oxidising properties:Corrosive to metals:Heat of combustion:		Colourless
Volatility:Boiling point at atmospheric pressureVapour pressure at 20 °C:Vapour pressure at 50 °C:Evaporation rate at 20 °C:Product description:Density at 20 °C:Relative density at 20 °C:Kinematic viscosity at 20 °C:Kinematic viscosity at 20 °C:Kinematic viscosity at 20 °C:Kinematic viscosity at 40 °C:Concentration:pH:Vapour density at 20 °C:Partition coefficient n-octanol/waterSolubility in water at 20 °C:Solubility properties:Decomposition temperature:Melting point/freezing point:Flammability:Flash Point:Flammability (solid, gas):Autoignition temperature:Lower flammability limit:Upper flammability limit:Upper flammability limit:Ipper flammability limit:Corrosive properties:Oxidising properties:Oxidising properties:Corrosive to metals:Heat of combustion:		Characteristic
 Boiling point at atmospheric pressure Vapour pressure at 20 °C: Vapour pressure at 20 °C: Evaporation rate at 20 °C: Product description: Density at 20 °C: Relative density at 20 °C: Dynamic viscosity at 20 °C: Kinematic viscosity at 20 °C: Kinematic viscosity at 40 °C: Concentration: pH: Vapour density at 20 °C: Partition coefficient n-octanol/water Solubility in water at 20 °C: Solubility properties: Decomposition temperature: Melting point/freezing point: Flammability: Flash Point: Flammability (solid, gas): Autoignition temperature: Lower flammability limit: Upper flammability limit: Particle characteristics: Median equivalent diameter: 2 Other information: Information with regard to physe Explosive properties: Corrosive to metals: Heat of combustion: 		Non-applicable *
 Vapour pressure at 20 °C: Vapour pressure at 50 °C: Evaporation rate at 20 °C: Product description: Density at 20 °C: Relative density at 20 °C: Dynamic viscosity at 20 °C: Kinematic viscosity at 20 °C: Kinematic viscosity at 40 °C: Concentration: pH: Vapour density at 20 °C: Partition coefficient n-octanol/water Solubility in water at 20 °C: Solubility properties: Decomposition temperature: Melting point/freezing point: Flammability: Flash Point: Flammability (solid, gas): Autoignition temperature: Lower flammability limit: Upper flammability limit: Upper flammability limit: Particle characteristics: Median equivalent diameter: 2 Other information: Information with regard to physe Explosive properties: Oxidising properties: Corrosive to metals: Heat of combustion: 		
 Vapour pressure at 50 °C: Evaporation rate at 20 °C: Product description: Density at 20 °C: Relative density at 20 °C: Dynamic viscosity at 20 °C: Kinematic viscosity at 20 °C: Kinematic viscosity at 40 °C: Concentration: pH: Vapour density at 20 °C: Partition coefficient n-octanol/water Solubility in water at 20 °C: Solubility properties: Decomposition temperature: Melting point/freezing point: Flammability: Flash Point: Flammability (solid, gas): Autoignition temperature: Lower flammability limit: Upper flammability limit: Upper flammability limit: Tarticle characteristics: Median equivalent diameter: 2 Other information: Information with regard to physe Explosive properties: Oxidising properties: Corrosive to metals: Heat of combustion: 	:	Non-applicable *
Evaporation rate at 20 °C: Product description: Density at 20 °C: Relative density at 20 °C: Dynamic viscosity at 20 °C: Kinematic viscosity at 20 °C: Kinematic viscosity at 40 °C: Concentration: pH: Vapour density at 20 °C: Partition coefficient n-octanol/water Solubility in water at 20 °C: Solubility properties: Decomposition temperature: Melting point/freezing point: Flammability: Flash Point: Flammability (solid, gas): Autoignition temperature: Lower flammability limit: Upper flammability limit: Upper flammability limit: Particle characteristics: Median equivalent diameter: 2 Other information: Information with regard to phys Explosive properties: Oxidising properties: Corrosive to metals: Heat of combustion:		2344 Pa
 Product description: Density at 20 °C: Relative density at 20 °C: Dynamic viscosity at 20 °C: Kinematic viscosity at 20 °C: Kinematic viscosity at 40 °C: Concentration: pH: Vapour density at 20 °C: Partition coefficient n-octanol/water Solubility in water at 20 °C: Solubility properties: Decomposition temperature: Melting point/freezing point: Flammability: Flash Point: Flammability (solid, gas): Autoignition temperature: Lower flammability limit: Upper flammability limit: Upper flammability limit: Particle characteristics: Median equivalent diameter: 2 Other information: Information with regard to physe Explosive properties: Oxidising properties: Corrosive to metals: Heat of combustion: 		Non-applicable *
Density at 20 °C: Relative density at 20 °C: Dynamic viscosity at 20 °C: Kinematic viscosity at 20 °C: Kinematic viscosity at 40 °C: Concentration: pH: Vapour density at 20 °C: Partition coefficient n-octanol/water Solubility in water at 20 °C: Solubility properties: Decomposition temperature: Melting point/freezing point: Flammability: Flash Point: Flammability (solid, gas): Autoignition temperature: Lower flammability limit: Upper flammability limit: Upper flammability limit: Particle characteristics: Median equivalent diameter: 2 Other information: Information with regard to physe Explosive properties: Oxidising properties: Corrosive to metals: Heat of combustion:		Non-applicable *
 Relative density at 20 °C: Dynamic viscosity at 20 °C: Kinematic viscosity at 20 °C: Kinematic viscosity at 40 °C: Concentration: pH: Vapour density at 20 °C: Partition coefficient n-octanol/water Solubility in water at 20 °C: Solubility properties: Decomposition temperature: Melting point/freezing point: Flammability: Flash Point: Flammability (solid, gas): Autoignition temperature: Lower flammability limit: Upper flammability limit: Particle characteristics: Median equivalent diameter: 2 Other information: Information with regard to physe Explosive properties: Oxidising properties: Corrosive to metals: Heat of combustion: 		
 Dynamic viscosity at 20 °C: Kinematic viscosity at 20 °C: Kinematic viscosity at 40 °C: Concentration: pH: Vapour density at 20 °C: Partition coefficient n-octanol/water Solubility in water at 20 °C: Solubility properties: Decomposition temperature: Melting point/freezing point: Flammability: Flash Point: Flammability (solid, gas): Autoignition temperature: Lower flammability limit: Upper flammability limit: Upper flammability limit: Particle characteristics: Median equivalent diameter: 2 Other information: Information with regard to physe Explosive properties: Oxidising properties: Corrosive to metals: Heat of combustion: 		1065,6 kg/m ³
 Kinematic viscosity at 20 °C: Kinematic viscosity at 40 °C: Concentration: pH: Vapour density at 20 °C: Partition coefficient n-octanol/water Solubility in water at 20 °C: Solubility properties: Decomposition temperature: Melting point/freezing point: Flammability: Flash Point: Flammability (solid, gas): Autoignition temperature: Lower flammability limit: Upper flammability limit: Particle characteristics: Median equivalent diameter: 2 Other information: Information with regard to physe Explosive properties: Oxidising properties: Corrosive to metals: Heat of combustion: 		1 - 1,1
 Kinematic viscosity at 40 °C: Concentration: pH: Vapour density at 20 °C: Partition coefficient n-octanol/water Solubility in water at 20 °C: Solubility properties: Decomposition temperature: Melting point/freezing point: Flammability: Flash Point: Flammability (solid, gas): Autoignition temperature: Lower flammability limit: Upper flammability limit: Particle characteristics: Median equivalent diameter: 2 Other information: Information with regard to physe Explosive properties: Oxidising properties: Corrosive to metals: Heat of combustion: 		200 - 500 cP (Brookfield, 20 rpm)
Concentration: pH: Vapour density at 20 °C: Partition coefficient n-octanol/water Solubility in water at 20 °C: Solubility properties: Decomposition temperature: Melting point/freezing point: Flammability: Flash Point: Flammability (solid, gas): Autoignition temperature: Lower flammability limit: Upper flammability limit: Upper flammability limit: Upper flammability limit: Particle characteristics: Median equivalent diameter: 2 Other information: Information with regard to physe Explosive properties: Oxidising properties: Corrosive to metals: Heat of combustion:		Non-applicable *
pH: Vapour density at 20 °C: Partition coefficient n-octanol/water Solubility in water at 20 °C: Solubility properties: Decomposition temperature: Melting point/freezing point: Flammability: Flash Point: Flammability (solid, gas): Autoignition temperature: Lower flammability limit: Upper flammability limit: Upper flammability limit: Particle characteristics: Median equivalent diameter: 2 Other information: Information with regard to phys Explosive properties: Oxidising properties: Corrosive to metals: Heat of combustion:		Non-applicable *
 Vapour density at 20 °C: Partition coefficient n-octanol/water Solubility in water at 20 °C: Solubility properties: Decomposition temperature: Melting point/freezing point: Flammability: Flash Point: Flammability (solid, gas): Autoignition temperature: Lower flammability limit: Upper flammability limit: Particle characteristics: Median equivalent diameter: 2 Other information: Information with regard to physe Explosive properties: Oxidising properties: Corrosive to metals: Heat of combustion: 		Non-applicable *
 Partition coefficient n-octanol/water Solubility in water at 20 °C: Solubility properties: Decomposition temperature: Melting point/freezing point: Flammability: Flash Point: Flammability (solid, gas): Autoignition temperature: Lower flammability limit: Upper flammability limit: Upper flammability limit: Particle characteristics: Median equivalent diameter: 2 Other information: Information with regard to physe Explosive properties: Oxidising properties: Corrosive to metals: Heat of combustion: 		7,5 - 8,5
Solubility in water at 20 °C: Solubility properties: Decomposition temperature: Melting point/freezing point: Flammability: Flash Point: Flammability (solid, gas): Autoignition temperature: Lower flammability limit: Upper flammability limit: Particle characteristics: Median equivalent diameter: 2 Other information: Information with regard to phys Explosive properties: Oxidising properties: Corrosive to metals: Heat of combustion:		Non-applicable *
 Solubility properties: Decomposition temperature: Melting point/freezing point: Flammability: Flash Point: Flammability (solid, gas): Autoignition temperature: Lower flammability limit: Upper flammability limit: Upper flammability limit: Particle characteristics: Median equivalent diameter: 2 Other information: Information with regard to physe Explosive properties: Oxidising properties: Corrosive to metals: Heat of combustion: 	20 °C:	Non-applicable *
Decomposition temperature: Melting point/freezing point: Flammability: Flash Point: Flammability (solid, gas): Autoignition temperature: Lower flammability limit: Upper flammability limit: Upper flammability limit: Particle characteristics: Median equivalent diameter: 2 Other information: Information with regard to phys Explosive properties: Oxidising properties: Corrosive to metals: Heat of combustion:		Non-applicable *
 Melting point/freezing point: Flammability: Flash Point: Flammability (solid, gas): Autoignition temperature: Lower flammability limit: Upper flammability limit: Particle characteristics: Median equivalent diameter: 2 Other information: Information with regard to physe Explosive properties: Oxidising properties: Corrosive to metals: Heat of combustion: 		Non-applicable *
 Flammability: Flash Point: Flammability (solid, gas): Autoignition temperature: Lower flammability limit: Upper flammability limit: Particle characteristics: Median equivalent diameter: 2 Other information: Information with regard to physe Explosive properties: Oxidising properties: Corrosive to metals: Heat of combustion: 		Non-applicable *
 Flash Point: Flammability (solid, gas): Autoignition temperature: Lower flammability limit: Upper flammability limit: Particle characteristics: Median equivalent diameter: 2 Other information: Information with regard to physical explosive properties: Oxidising properties: Corrosive to metals: Heat of combustion: 		Non-applicable *
 Flammability (solid, gas): Autoignition temperature: Lower flammability limit: Upper flammability limit: Particle characteristics: Median equivalent diameter: 2 Other information: Information with regard to physe Explosive properties: Oxidising properties: Corrosive to metals: Heat of combustion: 		
 Autoignition temperature: Lower flammability limit: Upper flammability limit: Particle characteristics: Median equivalent diameter: 2 Other information: Information with regard to physe Explosive properties: Oxidising properties: Corrosive to metals: Heat of combustion: 		Non Flammable (>60 °C)
Lower flammability limit: Upper flammability limit: Particle characteristics: Median equivalent diameter: 2 Other information: Information with regard to phys Explosive properties: Oxidising properties: Corrosive to metals: Heat of combustion:		Non-applicable *
Upper flammability limit: Particle characteristics: Median equivalent diameter: 2 Other information: Information with regard to physical Explosive properties: Oxidising properties: Corrosive to metals: Heat of combustion:		Non-applicable *
 Particle characteristics: Median equivalent diameter: Other information: Information with regard to physical Explosive properties: Oxidising properties: Corrosive to metals: Heat of combustion: 		Non-applicable *
Median equivalent diameter: 2 Other information: Information with regard to physical Explosive properties: Oxidising properties: Corrosive to metals: Heat of combustion:		Non-applicable *
2 Other information: Information with regard to physe Explosive properties: Oxidising properties: Corrosive to metals: Heat of combustion:		
Information with regard to physe Explosive properties: Oxidising properties: Corrosive to metals: Heat of combustion:		Non-applicable
Explosive properties: Oxidising properties: Corrosive to metals: Heat of combustion:		
Oxidising properties: Corrosive to metals: Heat of combustion:	cal hazard cla	isses:
Corrosive to metals: Heat of combustion:		Non-applicable *
Heat of combustion:		Non-applicable *
		Non-applicable *
		Non-applicable *
Aerosols-total percentage (by mass) components:	of flammable	Non-applicable *
Other safety characteristics:		
Surface tension at 20 °C: Refraction index:		Non-applicable * Non-applicable *



Safety data sheet This SDS is an English translation of Regulation (EU) nº 2020/878, without any country-specific legislation

2WBL-IN/EX-M105 Granit Lakk Aqua

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

10.5 Incompatible materials:

	Acids	Water	Oxidising materials	Combustible materials	Others
Γ	Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION**

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
 - Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

Revised: 20/06/2023

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3. IARC: Non-applicable
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:



SECTION 11: TOXICOLOGICAL INFORMATION** (continued)

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus	
1,2-benzisothiazol-3(2H)-one	LD50 oral	500 mg/kg	Rat	
CAS: 2634-33-5	LD50 dermal	Non-applicable		
EC: 220-120-9	LC50 inhalation	Non-applicable		
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	LD50 oral	64 mg/kg	Rat	
CAS: 55965-84-9	LD50 dermal	87,12 mg/kg	Rabbit	
EC: Non-applicable	LC50 inhalation	0,33 mg/L (4 h)	Rat	
2-methylisothiazol-3(2H)-one	LD50 oral	120 mg/kg	Rat	
CAS: 2682-20-4	LD50 dermal	242 mg/kg	Rat	
EC: 220-239-6	LC50 inhalation	Non-applicable		

SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus	
1,2-benzisothiazol-3(2H)-one	LC50	>0.1 - 1 mg/L (96 h)		Fish	
CAS: 2634-33-5	EC50	>0.1 - 1 mg/L (48 h)		Crustacean	
EC: 220-120-9	EC50	>0.1 - 1 mg/L (72 h)		Algae	
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2- methyl-2H-isothiazol-3-one (3:1)	LC50	>0.1 - 1 mg/L (96 h)		Fish	
CAS: 55965-84-9	EC50	>0.1 - 1 mg/L (48 h)		Crustacean	
EC: Non-applicable	EC50	>0.1 - 1 mg/L (72 h)		Algae	
2-methylisothiazol-3(2H)-one	LC50	4,77 mg/L (96 h)	Oncorhynchus mykiss	Fish	
CAS: 2682-20-4	EC50	0,934 mg/L (48 h)	Daphnia magna	Crustacean	
EC: 220-239-6	EC50	Non-applicable			
Chronic toxicity:					
Identification		Concentration	Species	Genus	
2-mothylicothiazol_3(2H)-ono	NOEC	4.93 mg/l	Oncorbynchus mykics	Fich	

2.2	Persistence and degradability:				
	CAS: 2682-20-4 EC: 220-239-6	NOEC	0,044 mg/L	Daphnia magna	Crustacean
	2-methylisothiazol-3(2H)-one	NOEC	4,93 mg/L	Oncorhynchus mykiss	Fish
	Identification		concentration	Species	Genus

12.2 Pers



SECTION 12: ECOLOGICAL INFORMATION** (continued) Substance-specific information: Identification Degradability Biodegradability 1,2-benzisothiazol-3(2H)-one BOD5 Concentration 100 mg/L Non-applicable COD CAS: 2634-33-5 Non-applicable Period 28 days BOD5/COD EC: 220-120-9 Non-applicable % Biodegradable 0 % 2-methylisothiazol-3(2H)-one BOD5 Non-applicable Concentration 10 mg/L COD CAS: 2682-20-4 Non-applicable Period 28 days BOD5/COD % Biodegradable EC: 220-239-6 Non-applicable 55,8 % 12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential		
1,2-benzisothiazol-3(2H)-one	BCF	2	
CAS: 2634-33-5	Pow Log	1.45	
EC: 220-120-9	Potential	Low	
2-methylisothiazol-3(2H)-one	BCF		
CAS: 2682-20-4	Pow Log	-0.49	
EC: 220-239-6	Potential		

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
2-methylisothiazol-3(2H)-one	Кос	Non-applicable	Henry	0E+0 Pa·m ³ /mol
CAS: 2682-20-4	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 220-239-6	Surface tension	Non-applicable	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 12	waste paint and varnish other than those mentioned in 08 01 11	Non dangerous

Type of waste (Regulation (EU) No 1357/2014):

Non-applicable

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See subsection 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)



SECTION 15: REGULATORY INFORMATION**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains 1,2benzisothiazol-3(2H)-one, Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), bronopol (INN), 2-methylisothiazol-3(2H)-one.

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: 1,2-benzisothiazol-3(2H)-one (Product-type 2, 6, 9, 11, 12, 13) ; Reaction mass of 5chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (Product-type 2, 4, 6, 11, 12, 13) ; 2-methylisothiazol-3(2H)-one (Product-type 6, 11, 12, 13)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Non-applicable

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION**

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

SECTION 2, SECTION 3, SECTION 8, SECTION 11, SECTION 12, SECTION 15, SECTION 16

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 2: H310+H330 - Fatal in contact with skin or if inhaled.

Acute Tox. 2: H330 - Fatal if inhaled.

Acute Tox. 3: H301 - Toxic if swallowed.

Acute Tox. 3: H301+H311 - Toxic if swallowed or in contact with skin.

Acute Tox. 4: H302 - Harmful if swallowed.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects. Eye Dam. 1: H318 - Causes serious eye damage.

Chin Com 1D 1214 Courses serious eye utiliage.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage. Skin Corr. 1C: H314 - Causes severe skin burns and eye damage.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Skin Sens. 1A: H317 - May cause an allergic skin reaction.

Classification procedure:

Non-applicable

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.



SECTION 16: OTHER INFORMATION** (continued)

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5day biochemical oxygen demand BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 LOgPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon UFI: unique formula identifier IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -