



Windoora

Window and door paint

- ✓ Innovative product on the basis of water-based alkyd
- ✓ Semi gloss
- ✓ Snow white



Description	
Properties	<p>New generation water-borne enamel that does not contain solvents</p> <ul style="list-style-type: none"> ✓ Creates an ideally smooth snow-white semi-gloss coating. ✓ Combines the best properties of alkyd and water-based enamel due to the water-borne alkyd binder: <ul style="list-style-type: none"> - excellent mechanical film properties – high hardness, wash resistance and water resistance; - does not contain volatile organic solvents - odourless - dries quickly - anti-blocking – the coating loses its adhesive capacity as it dries - non-flammable, non-combustible and non-explosive ✓ Excellent coverage ✓ The painted surface can withstand frequent wet cleaning with detergents <p>Maximum permissible EU VOC content for this product (subcat. d): 130g/L; maximum VOC content in the product <130g/L. Gloss:</p> <ul style="list-style-type: none"> • Semi-gloss in accordance with EN 13300 <p>Wash resistance:</p> <ul style="list-style-type: none"> • class 1 in accordance with EN 13300
Purpose	<p>For interior and exterior painting of wooden window frames, window sills and sashes, doors, door frames, window trimmers, bungalow furniture and other new or previously painted surfaces made of wood, wood chipboard, wood fibre board etc. Not recommended for painting floors or thresholds.</p>
Types of surfaces for painting	<p>Wooden surfaces, gypsum board panels, surfaces filled with putty or plastered. Also suitable for primed metal surfaces indoors.</p>

Quality standards and labels	<ul style="list-style-type: none"> ✓ EN 13300 [Paints and varnishes. Water-borne coating materials and coating systems for interior walls and ceilings. Classification] – classification standards of coverage, gloss level and wet abrasion resistance parameters for water-borne coating materials for interior walls and ceilings. ✓ VOC (volatile organic compounds) – content in accordance with the European Union directive 2004/42/CE ✓ Product and service quality is guaranteed by the quality, environmental protection, occupational health and safety management system in accordance with standards ISO 9001:2015; ISO 14001:2015 and ISO 45001:2018
Product specifications	
Surface preparation before painting	The surface to be painted must be degreased and cleaned from peeling paint, dirt and dust; it must also be dry (moisture content must not exceed 20%). Clean the surface from dirt, sawdust or grease. Scrub the places affected by mould with a brush or scraper and treat with the Biotol E product. Remove peeling paint and rust stains (for example, those left by screw heads). Clean dirty surface with agent EasyClean. Hard glossy surfaces should be sanded until they are matt. Use the OPS PRO product for the removal of old varnish coatings if necessary. Impregnate the entire wooden surface to be painted with the product Aura Biostop or Biostop Aqua. If there are any knots on the surface, remove resin and treat the knots with isolating varnish.
Application	Stir the paint thoroughly before application. Mixing a sufficient quantity of the tinted paint from several cans in one container is recommended for ensuring that the colour of large surfaces is even. Apply 1-2 coats with a brush or roller at the temperature between +10 °C and +22 °C and relative humidity not exceeding 80%. Application in the conditions of exposure to direct sunlight, draughts and high temperature can cause surface defects.
Care for the painted surface	The coating reaches its peak wash resistance in about 4 weeks; in the meantime, treat the surface with care until its hardness and wash resistance have reached their peak levels. If necessary, the surface can be lightly wiped with a soft sponge or cloth approximately 48 hours after paint application. We recommend using water and neutral or medium alkaline detergents (pH below 9) for cleaning. Do not use organic solvents, abrasive cleansers and hard scrubbing brushes or sponges. We recommend using Biotol E and Biotol Spray to remove mould.
Colour	White
Tinting	Machine tinting according to the Eskarocolor system (base A)
Consumption (one layer)	6–10 m ² /L
Thinner	Water
Drying time	No sooner than 10 hours later can apply a new layer, at the temperature of +20 °C and the relative humidity of 65%. If the temperature is lower and the humidity is higher, the drying takes longer accordingly.
Tools	Brush, roller.
Tool cleaning	Clean the tools with water after completing work.
Additional information	
Frost resistance	Not frost-resistant
Min shelf life	2 years
Storage conditions	Store in a tightly closed container at the temperature between +5 °C and +30 °C. Protect from exposure to freezing and direct sunlight.
Safety precautions	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains 1,2-benzisothiazol-3(2H)-one, Cobalt bis(2-ethylhexanoate). May produce an allergic reaction. Keep out of reach of children. When operating, follow working safety standards and requirements. As a preventative measure it is recommended to use basic Personal Protection Equipment.
Waste treatment	Avoid release to the environment. Dispose of the contents/containers in accordance with the current legislation on waste treatment. Waste treatment methods: code 08 01 12- Waste paint and varnish other than those mentioned in 08 01 11, waste class (Regulation (EU) No 1357/2014): non-dangerous.
Density	1,3kg/L
Volume/weight:	0,45 L - 0,9 L – 2,7 L
<p>The information concerning the product is based on the results of laboratory tests and practical use of the product depending on the location and conditions of its use. As the manufacturer, we guarantee the quality of the product and provide the best recommendations for its appropriate application. As the manufacturer, we cannot control the conditions and circumstances of product transportation, storage and application and numerous other factors that affect its use. Thus, we shall not bear responsibility for the damage caused by ignoring the instructions for use or transportation, by noncompliance with storage conditions and timeframes or by inappropriate application of the product. The manufacturer reserves the right to alter product information at their discretion without prior notice. For additional information, please contact us: http://eskaroo.ee/kontaktid/main_office_contacts/</p>	