



Linaõli

- ✓ 100% linseed oil



Description	
Properties	<p>Refined cold-pressed linseed oil for wood impregnation and treatment.</p> <ul style="list-style-type: none"> ✓ Pleasant natural oil scent ✓ Enhances the beauty of wood, giving it a light silky sheen ✓ Prevents wood from cracking ✓ Protects the surface from dirt and moisture ✓ Contains no biocides or solvents ✓ Perfect for treating handmade wooden items ✓ Suitable for items that come into contact with food
Purpose	Wood products and wooden constructions, toys, cutting boards, spoons, furniture, pressed wood panels, and other wooden items. For indoor use. Not suitable for lacquered or painted surfaces.
Types of surfaces	Wood surfaces that have been cleaned of old, unstable coatings. Not suitable for treating floors.
Quality standards	<ul style="list-style-type: none"> ✓ The quality of products and services is ensured by an integrated management system for quality, environment, occupational health and safety, compliant with the requirements of ISO 9001:2015, ISO 14001:2015, and ISO 45001:2018 standards.
Product specifications	
Surface preparation	<p>The moisture content of the wood must not exceed 20%. The working temperature should be between +5...+25°C, with a maximum relative humidity of 80%. The surface to be treated must be thoroughly cleaned of dirt, grease, and dust. The wood surface must not show damage caused by mold. Surfaces affected by bluing or mold should be treated with Wood Cleaner or Biotol E (follow the product instructions). Previously painted surfaces must be thoroughly cleaned using a scraper, stiff-bristled brush, heat gun, or paint remover OPS 10.</p> <p>Darkened wood surfaces should be cleaned mechanically with a wire brush, and any rotten boards must be replaced with new ones. It is recommended to use galvanized fasteners for securing wooden elements.</p>
Application	Apply the oil to the surface using a clean cloth or brush and allow it to absorb for 15–30 minutes. For highly absorbent surfaces, repeat the treatment. Wipe off any oil that has not been absorbed with a cloth. For immersion treatment, place the wooden item into the oil, allow it to soak, and then remove any excess oil from the surface with a cloth.
Colour	Yellowish.
Consumption	8 - 12 m ² /L.
Thinner	Pine tärpentine.
Drying time	3 to 7 days (at a temperature of 20°C and relative humidity of 50%).

Tools	Brush, cloth.
Tool cleaning	Clean tools thoroughly with water and soap.
Additional information	
Frost resistance	None.
Storage conditions	Store and transport in a tightly sealed container at the temperature between +5...30 °C. Protect from exposure to freezing and direct sunlight.
Safety precautions	The product is not classified as hazardous according to the CLP Regulation (EC) No 1272/2008. Contains linseed oil. Spontaneous combustion of oily cloth or paper is possible. Oil-contaminated waste and cloths must be collected in a fireproof container and moistened with water. Keep out of reach of children.
Waste treatment	Paint products must always be handled with care. Avoid or minimize the generation of residues. Do not pour into the sewage system. Prevent release into the environment. Empty, dry packaging should be taken to a packaging waste collection point (Waste Code 15 01); dry product residues may be disposed of in household waste containers, while liquid residues must be handed over to a licensed waste handler. Information about waste handlers is available from the local municipality or the Environmental Board. For larger quantities, please contact the Estonian Recycling Organization MTÜ at eto@eto.ee .
Density	0,9 kg/L.
Volume/weight:	1 L – 3 L – 5 L
<p>The information concerning the product is based on the results of laboratory tests and practical use of the product depending on the location and conditions of its use. As the manufacturer, we guarantee the quality of the product and provide the best recommendations for its appropriate application. As the manufacturer, we cannot control the conditions and circumstances of product transportation, storage and application and numerous other factors that affect its use. Thus, we shall not bear responsibility for the damage caused by ignoring the instructions for use or transportation, by noncompliance with storage conditions and timeframes or by inappropriate application of the product. The manufacturer reserves the right to alter product information at their discretion without prior notice. For additional information, please contact us: http://eskaro.ee/kontaktid/main_office_contacts/</p>	