



Saunavaha Vihta

Decorative and protective agent for wooden sauna and interior surfaces

- ✓ Water-borne
- ✓ Creates a water-repellent and dirt-repellent coating
- ✓ Suitable for treating sauna benches
- ✓ Can be tinted. Manufacturer-supplied colours: white and black



Description	
Properties	Water-borne agent for the protection and decorative finish of wooden sauna and interior surfaces. ✓ Contains natural carnauba wax ✓ Creates a water-repellent and dirt-repellent coating ✓ Leaves the wood naturally breathable ✓ Maintains the attractive natural colour of the wood Maximum permissible EU VOC content for the product (subcat f): 130 g/L. Maximum VOC content in the product <130 g/L
Purpose	For treating wooden surfaces in saunas, washrooms, steam rooms, locker rooms, living rooms.
Types of surfaces	New untreated or previously treated and cleaned wooden surfaces: sauna benches, walls, ceilings, window frames, doors, sills, etc. The product is not suitable for surfaces previously treated with oil unless the oil has completely worn off. For interior use.
Quality standards and labels	✓ VOC (volatile organic compounds) – content in accordance with the European Union directive 2004/42/CE. ✓ Product and service quality is guaranteed by the quality, environmental protection, occupational health and safety management system in accordance with standards ISO 9001:2015; ISO 14001:2015 and ISO 45001:2018.
Product specifications	
Surface preparation before treatment	The surface must be clean and dry. Wood moisture content must not exceed 20%. Thoroughly clean the surface to be treated from wax, grease, dust and other impurities. Wash the surfaces previously treated with wax, using Easy Clean and dry. The product is not suitable for surfaces previously treated with oil unless the oil has completely worn off. If the surface has been previously treated with varnish or other sauna protection agent, make swatch in a discreet location first. Before treating new wooden surfaces, spray them with water, let them dry and sand the wood fibers which have risen. Make sure to remove all sanding dust. Use construction film to cover the surfaces that are not to be coated with wax (for instance, floors). Please follow the product application manual.
Application	Recommended work temperature up to +10 °C and relative humidity not exceeding 80%. Stir the product thoroughly before and during the application. Apply 1 or 2 coats (1 coat in steam rooms). Apply along the grain with a brush or sponge, without pauses, rubbing the wax in properly to avoid streaking. Treat sauna benches board by board. When using tinted wax, we recommend making a swatch on a small section of the wooden surface to check that the tint is suitable. The final colour of the surface will depend on wood species, number of knots, previous treatment and number of the coats applied. If the waxed surface needs to be painted over, use a similar agent or sand the surface to clean wood.

Care for the surface	The coating reaches its peak hardness in about 4 weeks; in the meantime, treat the surface with care until its hardness and wash resistance have reached their peak levels. We recommend using water and neutral or medium alkaline detergents (pH 6...8) for cleaning.
Colour	Transparent and manufacturer-supplied colours: white, black.
Tinting	Tintable with water-based colorants.
Dilution	The product is ready for use.
Consumption	9...13 m ² /L
Thinner	Water
Drying time	Dust-free drying time: 0.5 ... 2 hours; at the temperature between +20...23 °C and the relative humidity of 50%, the surface is fully dry in 24 hours. Heat and ventilate the sauna after wax application.
Tools	Brush, sponge.
Tool cleaning	Wash with soap and water after completing work.
Additional information	
Frost resistance	None
Storage conditions	Store in undamaged containers at the temperature between +5...+30 °C. Protect from freezing and direct sunlight.
Safety precautions	Contains 1,2-benzisothiazol-3(2H)-one, 2-methylisothiazol-3(2H)-one, 5-chloro-2-methyl-4-isothiazol-3-one and 2-methyl-2H-isothiazol-3- a mixture of ions. May produce an allergic reaction. If medical advice is needed, have product container or label at hand. Keep out of reach of children.
Waste treatment	Avoid release to the environment. Dispose of the contents/containers in accordance with the current legislation on waste treatment. Waste treatment methods: code 08 01 12- Waste paint and varnish other than those mentioned in 08 01 11, waste class (Regulation (EU) No 1357/2014): non-dangerous.
Density	1,02 kg/L.
Volume/weight:	0,45 L – 0,9 L
The information concerning the product is based on the results of laboratory tests and practical use of the product depending on the location and conditions of its use. As the manufacturer, we guarantee the quality of the product and provide the best recommendations for its appropriate application. As the manufacturer, we cannot control the conditions and circumstances of product transportation, storage and application and numerous other factors that affect its use. Thus, we shall not bear responsibility for the damage caused by ignoring the instructions for use or transportation, by noncompliance with storage conditions and timeframes or by inappropriate application of the product. The manufacturer reserves the right to alter product information at their discretion without prior notice. For additional information, please contact us http://eskaro.ee/kontaktid/main_office_contacts/	