



Cinderella

Highly dirt-repellent matt wall paint

- ✓ „Easy to clean“ – easy to clean from difficult dirt
- ✓ Provided with self-crosslinking dispersion
- ✓ Contains special solid fillers based on natural aluminosilicate
- ✓ Highest grade of wash resistance (Class I)



Description	
Properties	<p>Matt acrylate water-borne paint for wet and dry indoor areas.</p> <ul style="list-style-type: none"> ✓ Excellent opacity ✓ Easy applications without dripping or splatter; easy to level out ✓ The paint does not give off harmful substances into the air and has been classified as emission class M1 ✓ Suitable for sensitive and allergic people ✓ Exceptional decorative properties: provides a smooth dense matt non-porous coating ✓ Due to the self-crosslinking dispersion, the formed surface is stronger and less porous that prevents the penetration of complicated dirt (coffee, tea, fruit juices, wine, sauces, markers, watercolor paints, pencils, pens, lipstick, etc.) ✓ The exceptional mechanical strength of the coating is ensured by the use of a special natural aluminosilicate solid component ✓ Highest grade of wash resistance (Class I according to EN13300) ✓ Remove stains and dirt immediately after they appear ✓ Can withstand moderate rubbing without becoming glossy <p>Maximum permissible EU VOC content for the product: (subcat a) 30 g/L. Maximum VOC content in the product <10 g/L.</p> <p>Gloss:</p> <ul style="list-style-type: none"> • Matt (approximately 7) in accordance with EN 13300 • Group 5 according to RYL 2012 <p>Wash resistance:</p> <ul style="list-style-type: none"> • Class 1 in accordance with EN 13300 (ISO 11 998) • 315 group of painting products according to RYL 2012 <p>Indoor load class:</p> <ul style="list-style-type: none"> • RL 05 Special loads and requirements in humid interior spaces according to RYL 2012
Purpose	Painting walls in humid and wet indoor areas. Especially recommended for nurseries, school classrooms, hotels, kitchens and catering facilities. Do not use the coated surface for drawing! Not suitable for painting floors, doors or furniture.
Types of surfaces for painting	Previously painted or newly prepared for painting concrete, plaster, plasterboard surface, building blocks, fiberboard and chipboard surface.

Quality standards	<ul style="list-style-type: none"> ✓ EN 13300 [Paints and varnishes. Water-borne coating materials and coating systems for interior walls and ceilings. Classification] – classification standards of coverage, gloss level and wet abrasion resistance parameters for water-borne coating materials for interior walls and ceilings. ✓ VOC (volatile organic compounds) – content in accordance with the European Union directive 2004/42/CE. ✓ Product and service quality is guaranteed by the quality, environmental protection, occupational health and safety management system in accordance with standards ISO 9001:2015; ISO 14001:2015 and ISO 45001:2018. ✓ "Eesti Allergialiid tunnustab" ("Estonian Allergy and Asthma Federation recognizes") is assigned to products that are safe, reliable, do not contain fragrance or generally irritating or sensitising substances and that help to reduce indoor air pollutant levels and are suitable for people with sensitive skin or suffering from allergic diseases.
Product specifications	
Surface preparation before painting	The surface to be painted must be carefully cleaned from loose or peeling material, dirt, grease and dust. Sandpaper durable alkyd substrates until they are matt and remove the dust thoroughly. If the surface is very dirty, wash it with Easy Clean. Use a putty from the FILLER line to fill cracks, holes and uneven areas. Sand the filled surface to make it even and remove sanding dust. Prime filled surfaces with Aquastop or Tiegrund, in wet rooms with Aquastop Bio moisture barrier to reduce porosity. Follow the product instructions for use.
Application	Stir the paint thoroughly before application. Mixing tinted paint in one container is recommended. Apply 2 coats with a roller, brush or spray gun at the temperature between +10 °C and +25 °C and relative air humidity below 80%. When using a spray gun or for the application of the first coat, dilute the paint with water in the amount of 5% until it reaches working viscosity. Apply undiluted paint for the finishing coat. Avoid application in drafty places and at high air temperature (over +25 °C). When painting, make sure to keep a wet edge.
Care for the painted surface	<p>Under normal circumstances, the coating reaches its initial level of water-repellent (hydrophobic) protection within 1–2 weeks after application, so we do not recommend cleaning the painted surface during this period. In case the painted surface needs to be cleaned earlier, do it cautiously with a soft damp cloth. Remove stains and dirt immediately after they appear.</p> <p>Under normal circumstances, the coating reaches its peak wash resistance in 3–4 weeks, after which it can also withstand more vigorous cleaning. To clean the painted surface from dirt, use warm water and a soft washcloth or microfiber cloth. Do not use abrasive tools or detergents, stiff brushes or rough sponges.</p> <p>As a rule, the painted surface regains its water-repellent properties in 5–7 days after it is cleaned with a damp cloth, but the timeframe still depends on the detergent or tool used, on how vigorous the cleaning process is and how dirty the surface is. The use of a detergent may prevent the surface from regaining its hydrophobic properties. However, the absence of the paint's water-repellent properties will not reduce its resistance to washing.</p>
Colour	White.
Tinting	Machine tinting according to the Eskarocolor system (base A).
Dilution	The product is ready for use. Allowed dilution of 5% of the paint volume.
Consumption	Paint consumption on absorbent substrates is 7–8 m ² /L, on non-absorbent substrates 9–10 m ² /L.
Thinner	Water.
Drying time	At the temperature of +23 °C and the relative humidity of 50%, the surface is ready for the application of another coat in 1...1,5 hours.
Tools	Roller, airless spray gun, brush.
Tool cleaning	Wash with soap and water after completing work.
Additional information	
Frost resistance	None.
Storage conditions	Store and transport in a tightly sealed container at the temperature between +5...30 °C. Protect from exposure to freezing and direct sunlight.
Safety precautions	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains 1,2-benzisothiazol-3(2H)-one, 2-methylisothiazol-3(2H)-one, Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. If medical advice is needed, have product container or label at hand. Keep out of reach of children.
Waste treatment	Avoid release to the environment. Dispose of the contents/containers in accordance with the current legislation on waste treatment. Waste treatment methods: code 08 01 12- Waste paint and varnish other than those mentioned in 08 01 11, waste class (Regulation (EU) No 1357/2014): non-dangerous.
Density	1,24 kg/L.
Volume/weight:	0,9 L – 2,7 L – 9 L
<p>The information concerning the product is based on the results of laboratory tests and practical use of the product depending on the location and conditions of its use. As the manufacturer, we guarantee the quality of the product and provide the best recommendations for its appropriate application. As the manufacturer, we cannot control the conditions and circumstances of product transportation, storage and application and numerous other factors that affect its use. Thus, we shall not bear responsibility for the damage caused by ignoring the instructions for use or transportation, by noncompliance with storage conditions and timeframes or by inappropriate application of the product. The manufacturer reserves the right to alter product information at their discretion without prior notice. For additional information, please contact us: http://eskaro.ee/kontaktid/main_office_contacts/</p>	