



Objekt Plus

Insulating primer

- ✓ Mat
- ✓ Effectively isolates dirt and stains
- ✓ Excellent adhesion and coverage
- ✓ Painter's white



| Description | |
|--------------------------------|---|
| Properties | <p>Water-based, matte acrylic primer paint for heavily soiled ceilings and walls in indoors.</p> <ul style="list-style-type: none"> ✓ Effectively isolates nicotine, smoke, soot, tar, rust, grease, oil, household dirt stains, graffiti, tannin, water damage marks, and other dirt ✓ Good coverage. Quickly and effectively coats soiled surfaces ✓ Good adhesion to various surfaces, including those previously painted with alkyd and oil-based paints ✓ Easily sandable ✓ Suitable for spot priming ✓ Protects the surface from yellowing. Prevents substances that cause wood yellowing from penetrating through the paint layer ✓ Fast drying ✓ Almost odourless <p>EU VOC (Volatile Organic Compound) content limit for the subcategory: 30 g/L. Maximum VOC content in ready-to-use paint: <30 g/L.</p> <p>Gloss:</p> <ul style="list-style-type: none"> • Mat (approx.. 7) according to EN 13300. <p>Wet scrub resistance:</p> <ul style="list-style-type: none"> • 1. class according to EN 13300 (ISO 11 998). |
| Purpose | For painting heavily soiled ceilings and walls in indoor areas (entrances, hallways, kitchens, living rooms, offices, classrooms, hotels, and other household and workspaces). Suitable for priming bright surfaces. Intended as a primer under water-based surface paints (e.g., Akrit, Akzent, Cinderella, Mattilda, ESK PRO, etc.). May remain the final finishing coat in areas where high abrasion or water resistance is not required. Not suitable for painting furniture, floors or doors. |
| Types of surfaces for painting | Previously painted or newly prepared for painting concrete, plaster, plasterboard surface, building blocks, fiberboard, chipboard surface, OSB, fiberboard, particleboard, paneling, and puttied surfaces. For interior use. |
| Quality standards | <ul style="list-style-type: none"> ✓ EN 13300 [Paints and varnishes. Water-borne coating materials and coating systems for interior walls and ceilings. Classification] – classification standards of coverage, gloss level and wet abrasion resistance parameters for water-borne coating materials for interior walls and ceilings. ✓ ISO 11 998, ISO 2813 – methods for determining gloss level and abrasion resistance. ✓ VOC (volatile organic compounds) – content in accordance with the European Union directive 2004/42/CE. ✓ Product and service quality is guaranteed by the quality, environmental protection, occupational health and safety management system in accordance with standards ISO 9001:2015; ISO 14001:2015 and ISO 45001:2018. |

| Product specifications | |
|---|---|
| Surface preparation before painting | The surface to be painted must be dry and thoroughly cleaned of unstable materials, grease, and dust. Use EasyClean or alkaline cleaning agents for cleaning, then rinse carefully with clean water and allow to dry. If necessary, use Biotol E or Biotol Spray to remove mold. Irregularities, cracks, and dents should be filled with a suitable filler from the FILLER series. Putty-coated surfaces, porous or unevenly porous surfaces should be primed with a moisture barrier such as Aquastop or Tiefgrund. Follow the product instructions accordingly. |
| Application | Before use, mix the paint thoroughly. Apply 1-2 coats depending on the surface's level of soiling. Apply using a brush, roller, or sprayer at a temperature of +10...25°C and relative humidity below 80%. Avoid drafts and high temperatures (above 25°C) during painting. |
| Care for the painted surface | The surface can be cleaned 4 weeks after painting, during which time it will achieve its final hardness and abrasion resistance. Use a damp soft sponge or cloth for cleaning the surface. Do not use abrasive cleaning agents or rough sponges or brushes. Cleaning agents containing organic solvents are not suitable. For mold removal, use Biotol E or Biotol Spray. |
| Colour | Painter's white. |
| Dilution | The product is ready to use and should not be diluted. Dilution may affect its coverage capability. |
| Consumption (1 layer) | 6-10 m²/L. |
| Thinner | Water. |
| Drying time | Repaintable in 6 hours, fully dried in 24 hours at a temperature of +23°C and a relative humidity of 50%. At lower temperatures and higher humidity, the drying time increases. |
| Tools | Brush, roller, airless spray gun. |
| Tool cleaning | Remove excess paint from the tool and wash clean with soap and water immediately after painting. |
| Additional information | |
| Frost resistance | None. |
| Storage conditions | Store and transport in a tightly sealed container at the temperature between +5...30 °C. Protect from exposure to freezing and direct sunlight. |
| Safety precautions | Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains 1,2-benzisothiazol-3(2H)-one, 2-methylisothiazol-3(2H)-one, Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. If medical advice is needed, have product container or label at hand. Keep out of reach of children. |
| Waste treatment | Avoid release to the environment. Dispose of the contents/containers in accordance with the current legislation on waste treatment. Waste treatment methods: code 08 01 12- Waste paint and varnish other than those mentioned in 08 01 11, waste class (Regulation (EU) No 1357/2014): non-dangerous. |
| Density | 1,2 kg/L. |
| Volume/weight: | 0,9L – 2,7L – 9L |
| The information concerning the product is based on the results of laboratory tests and practical use of the product depending on the location and conditions of its use. As the manufacturer, we guarantee the quality of the product and provide the best recommendations for its appropriate application. As the manufacturer, we cannot control the conditions and circumstances of product transportation, storage and application and numerous other factors that affect its use. Thus, we shall not bear responsibility for the damage caused by ignoring the instructions for use or transportation, by noncompliance with storage conditions and timeframes or by inappropriate application of the product. The manufacturer reserves the right to alter product information at their discretion without prior notice. For additional information, please contact us: https://eskaro.ee/en/contact/ | |