



EMISSION CLASS
M1
BUILDING MATERIALS



Description	
Properties	<p>White, semi-matte, water-based acrylic paint for painting interior lining boards, wooden ceilings and walls indoors.</p> <ul style="list-style-type: none"> With good coverage For painting wooden ceilings and walls Quick drying Tintable The paint does not give off harmful substances into the air and has been classified as emission class M1 <p>Maximum permissible EU VOC content for this product (subcat. d): 130g/L; maximum VOC content in the product <130g/L.</p>
Types of surfaces for painting	New and previously painted or varnished wooden ceiling and wooden wall surfaces indoors.
Quality standards and labels	<ul style="list-style-type: none"> EN 13300 [Paints and varnishes. Water-borne coating materials and coating systems for interior walls and ceilings. Classification] – classification standards of coverage, gloss level and wet abrasion resistance parameters for water-borne coating materials for interior walls and ceilings. Product and service quality is guaranteed by the quality, environmental protection, occupational health and safety management system in accordance with standards ISO 9001:2015; ISO 14001:2015 and ISO 45001:2018.
Product specifications	
Surface preparation before painting	The surface must be dry (moisture content below 18%) and carefully cleaned of dirt, grease, dust, non-permanent and exfoliating material. If necessary, use Biotol E or Biotol Spray to remove mold. Clean the resin from the branches and cover with the primer Kruntex or Luotto Tartuntapohja Aqua. Sand previously painted or varnished glossy surfaces to a matt finish. Carefully remove the sanding dust. Follow the instructions for use of the products mentioned above.

Application	Mix the paint thoroughly before use. If necessary, the paint can be diluted with water (up to 5% of the volume). Apply 1-2 layers to the surface with a synthetic brush. When painting, try to maintain a "wet edge". Painting the second layer preferably after 4-5 hours. Darkened wooden surfaces should be primed with Kruntex or painted in several layers. It is advisable to paint new lining boards before installation. Operating temperature +8...+25°C and relative humidity below 80%.
Care for the painted surface	The coating reaches its peak wash resistance in about 4 weeks. In the meantime, treat the surface with care until its hardness and wash resistance have reached their peak levels. If necessary, the surface can be lightly wiped with a soft sponge or cloth approximately 48 hours after paint application. We recommend using water and neutral or medium alkaline detergents (pH below 9) for cleaning. Do not use organic solvents, abrasive cleansers and hard scrubbing brushes or sponges. Hard rubbing can make the surface glossy. The coating is resistant to solutions of detergents in water, to oils and greases, and short-term exposure to weak solvents (gasoline, white spirit).
Colour	White.
Dilution	Product is ready to use. The paint can be diluted with water in the amount of up to 5% of its volume.
Tinting	Machine tinting according to the Eskarocolor system (based A).
Consumption	6-8 m ² /L.
Thinner	Water.
Drying time	Dry to the touch for 1-2 hours, repaintable in 4-5 hours at a temperature of +23°C and a relative humidity of 50%. At lower temperatures and higher humidity, the drying time increases. The painted surface reaches its final wear resistance after 4 weeks.
Tools	Brush.
Tool cleaning	Clean the tools with water after completing work.
Additional information	
Frost resistance	Not frost-resistant.
Storage conditions	Store in a tightly closed container at the temperature between +5 °C and +35 °C. Protect from exposure to freezing and direct sunlight.
Safety precautions	Contains 1,2-benzisothiazol-3(2H)-one. May cause an allergic reaction. Warning! Hazardous inhalable droplets may form when sprayed. Do not inhale spray or mist. When contacting the doctor, take the product packaging or label with you. Keep out of the reach of children.
Waste treatment	Avoid release to the environment. Dispose of the contents/containers in accordance with the current legislation on waste treatment. Waste treatment methods: code 08 01 12- Waste paint and varnish other than those mentioned in 08 01 11, waste class (Regulation (EU) No 1357/2014): non-dangerous.
Density	1,2 kg/L.
Volume/weight	0,9L - 2,7L – 9L
The information concerning the product is based on the results of laboratory tests and practical use of the product depending on the location and conditions of its use. As the manufacturer, we guarantee the quality of the product and provide the best recommendations for its appropriate application. As the manufacturer, we cannot control the conditions and circumstances of product transportation, storage and application and numerous other factors that affect its use. Thus, we shall not bear responsibility for the damage caused by ignoring the instructions for use or transportation, by noncompliance with storage conditions and timeframes or by inappropriate application of the product. The manufacturer reserves the right to alter product information at their discretion without prior notice. For additional information, please contact us: https://eskaro.ee/en/contact/	