



## Sauna Oil

Protection for sauna benches

- ✓ Deep impregnation of the wood.
- ✓ Creates a water and dirt repellent coat
- ✓ Ensures that hygiene is maintained in the sauna.



Description	
Properties	<p>Oil- based product for long-term protection from moisture and dirt.</p> <ul style="list-style-type: none"> <li>✓ Penetrates the wood very well.</li> <li>✓ Makes the surface silky smooth.</li> <li>✓ Deepens the wood's natural colour depending on the type of wood and highlights its texture.</li> <li>✓ Ensures that hygiene is maintained in the sauna.</li> <li>✓ Creates a water-repellent and dirt-repellent coating.</li> <li>✓ The treated surfaces heat less and are easier to clean.</li> <li>✓ Does not obstruct the natural "breathing" of wood.</li> <li>✓ Odourless; does not change the characteristic "sauna" smell of the wood. Intended for surfaces in direct contact with people's skin.</li> </ul>
Purpose	For new untreated or previously oiled wooden surfaces
Surface types to be treated	Benches, head rests and back rests in saunas, etc.
Quality standards and labels	<ul style="list-style-type: none"> <li>✓ Product and service quality is guaranteed by the quality, environmental protection, occupational health and safety management system in accordance with standards ISO 9001:2015; ISO 14001:2015 and ISO 45001:2018.</li> </ul>
Product specifications	
Surface preparation before treatment	Clean dirty benches, rinse with water and dry them; then sand the surface and clean it from dust after sanding. The surface must be dry before application.
Application	Apply the product and let it absorb into the wood for 10–15 minutes. Perform application at temperatures over +5 °C and relative humidity below 80%. Repeat application if the surface is highly absorbing. Remove the residual product that has not been absorbed with a cloth. Heat the sauna for 1–2 hours and wipe off the product that has reappeared on the surface with a cloth.
Colour	Transparent.
Consumption	10–18 m <sup>2</sup> /L.
Drying time	The product is absorbed by wood, and the absorption rate depends on wood density.
Tools	Clean cloth, brush.

Tool cleaning	Wash with soap and water after completing work.
Information	
Frost resistance	None.
Storage conditions	Store and transport in undamaged containers at the temperature between +5 °C and +30 °C. Protect from freezing and direct sunlight.
Safety precautions	 <p><b>Danger.</b> May be fatal if swallowed and enters airways. If medical advice is needed, have product container or label at hand. Keep out of reach of children. IF SWALLOWED: Immediately call a POISON CENTER/doctor. UFI: G330-E0V0-500W-NAJU. Do NOT induce vomiting. Store locked up.</p>
Waste treatment	Avoid release to the environment. Dispose of the contents/containers in accordance with the current legislation on waste treatment. Waste treatment methods: code 08 01 11*- Waste paint and varnish containing organic solvents or other dangerous substances; waste class (Regulation (EU) No 1357/2014): dangerous.
Density	0.85 kg/L.
Volume/weight	0.4 L / 1L
<p>The information concerning the product is based on the results of laboratory tests and practical use of the product depending on the location and conditions of its use. As the manufacturer, we guarantee the quality of the product and provide the best recommendations for its appropriate application. As the manufacturer, we cannot control the conditions and circumstances of product transportation, storage and application and numerous other factors that affect its use. Thus, we shall not bear responsibility for the damage caused by ignoring the instructions for use or transportation, by noncompliance with storage conditions and timeframes or by inappropriate application of the product. The manufacturer reserves the right to alter product information at their discretion without prior notice. For additional information, please contact us: <a href="https://eskaro.ee/en/contact/">https://eskaro.ee/en/contact/</a></p>	